## R76LT

babco

Questions? Contact Babco's Sales Team info@babco.ca | 1-800-661-5313

**Tire Changer** SKU# 5140144 Tilt Back, 30" Capacity, 110 or 220V, 50/60hz

## Performs Masterfully on a Wide Variety of Wheels

The Ranger R76LT <u>tire changer</u> performs masterfully on a wide variety of wheels, including OEM configurations. This equipment has ergonomic controls, a tilt-back tower design, advanced clamp positioning and so much more.

This professional-grade Ranger R76LT is a tilt-tower machine. Its large turntable provides an internal clamping capacity of 30" and an external clamping capacity of 28". A sturdy body, rigid 45 mm hexagonal vertical shaft and hardened-steel horizontal outrigger support arm eliminate flex during all tire service procedures to reduce the likelihood of expensive wheels getting damaged. Bead seating and tire inflation is simple and effortless with Ranger's exclusive TurboBlast™ portable bead seating system.

## **Specifications**

Motor	2 HP (110 VAC 50-60 HZ) <b>or</b> 3 HP (220 VAC 50-60 HZ)
Drive System Type	Electric / Air
Air Requirement	110-175 PSI (8-12 BAR)
Wheel Clamping Method	4 Clamps - Internal / External
Table Clamping System	Dual Pneumatic Cylinders
Bead Breaking System	Adjustable Pneumatic Blade
Tower Design	Tilt-Back
Vertical Shaft / Tool Head	Pneumatic / Locking
Powerful Bead Seating System	TurboBlast™
Internal Rim Clamping Capacity	10" - 30" (254 mm - 762 mm)
External Rim Clamping Capacity	9" – 28" (229 mm - 711 mm)
Turntable Tire Width Capacity (Mounting)	4" - 18" (102 mm - 457 mm)
Bead Breaker Tire Width Capacity (Demounting)	1.5" - 16" (38 mm - 406 mm)
Maximum Tire Diameter	43" (1,092 mm)
Shipping Weight	886 lbs. (403 Kg)



## **Standard Features**

- Inflation System
- Inflation Gauge & Air Dump Valve
- Inflation Pressure Regulator/Limiter
- Water Filter
- Oiler / Lubricator
- Soap Brush

- Air Regulator
- Bead Tool/Tire Iron
- Alloy-Steel Mount-Demount Head
- Nylon Mount-Demount Head
- Large Soap Bucket
- Tool Tray / Storage