RML-1500XL



Motorcycle Lifts

SKU# 5150605 Motorcycle Lift Platform w/ Front Wheel Vise, Deluxe Extended Questions? Contact Babco's Sales Team info@babco.ca | 1-800-661-5313

Large Platform to Handle Virtually Any Motorcycle or ATV

With its wide, stable stance, stretched tabletop and super-tall lifting height, the RML-1500XL motorcycle and ATV lift greets you like the badass it is—rugged and tough with the muscle to prove it. We use rugged 12-gauge metal with superior welds and a durable powder-coat finish. Nope, wimpy is not on our list of features.

There are copycats everywhere, but just because it looks like a Ranger doesn't mean it works like a Ranger or lasts as long as a Ranger. Never trust a wannabe.

Features

- A combination of power, solid construction, and userfriendly features makes the Ranger RML-1500XL the best motorcycle lift money can buy
- With little effort, you can easily position, secure and raise motorcycles, bobbers, stretched choppers, trikes and other wheeled and recreational vehicles with ease
- Features 12-gauge welded-steel construction, a non-skid diamond-plate platform surface and full travel automatic safety locks that allow various working heights
- Side decks can be easily removed to provide a more compact work area for closer access to bikes when performing maintenance work or cleaning detail
- A humongous 1,500-lb. lifting capacity handles just about anything that rolls
- Safe and reliable means it's been lifecycle tested beyond industry standards
- Retractable, built-in, full-swivel casters provide stow-andgo capability even when loaded
- Precision ball bearings improve rollability
- A gentle slope, textured diamond-plate approach ramps, and a secondary cheater ramp means even ground huggers can be loaded effortlessly
- The RML-1500XL gets its power from a potent commercial-grade hydraulic power system that produces big lifting muscle right off the ground
- A dual-function power unit provides either air or hydraulic pump operation
- User-friendly controls increase productivity, reduce injuries, save money, and improve job satisfaction



Specifications

1,500 lbs. (682 kg)
7.5" (191 mm)
45" (1,143 mm)
89" (2,261 mm)
102" (2,591 mm)
30" (762 mm)
53" (1,346 mm)
126" (3,200 mm)
Air / Hydraulic
832 lbs. (377 kg)