

SP-7XEF

Full-Rise Scissor Lifts

SKU# 5175425

7,000-lb. Capacity / Scissor Lift / Frame Engaging / Flush Mount

babco

Questions? Contact Babco's Sales Team

info@babco.ca | 1-800-661-5313

The Flush-Mount Scissor Lift

If your garage has a recessed area of concrete designed to hold flush-mount lifts, you'll be pleased by how "invisible" this lift is in your garage. When it's collapsed, you're free to drive over it and work around it without tripping on wires or cables. We're proud that the collapsed SP-7XEF is extremely low-profile, but if you want to take low to virtually zero, the flush-mount version of this model is the perfect car lift solution for your garage.

Features

- Pneumatic safety locks
- Hardened pivot pins with "Zerk" fittings
- Open-center design
- Ergonomic controls
- Dual-cylinder hydraulic design provides extra power
- Low-profile
- Flush-mount



Specifications

Lifting Capacity	7,000 lbs. (3,175 kg)
Max. Lifting Height	70.5" (1,791 mm)
Overall Length	105.5" (2,692 mm)
Single Platform Length	62.5" (1,590 mm)
Single Platform Width	22" (554 mm)
Overall Width - Min	81.5" (2,072 mm)
Overall Width - Max	87.5" (2,222 mm)
Lowered Height	Flush with concrete
Lifting Time	45 sec
Standard Motor	208-240 VAC / 50-60 Hz / 1 Ph

Note: An air supply (minimum 30 psi / 3 CFM) is required for the safety-lock mechanisms to disengage. It is solely the responsibility of the end-user to provide, install and maintain the air supply.

Not all BendPak lift models meet the standards as prescribed by ANSI/ALI ALCTV-2017 or ANSI/UL 201. Consult www.autolift.org for complete listings.